
F A13HD 3/4 BSP

Codice articolo: **808300010** / **Female**



Valving style Flat face	**Body size** 1/2"
Sealing Nitrile NBR	**Treatment** Cr3
Interchange ISO 16028	**Connection system** Push
Disconnection system Pull back the sleeve	**Material** Carbon steel
Locking mechanism Locking ball + Safety lock	**Disconnectable under pressure** No
Thread FEMALE THREAD BSPP (ISO 1179-1)	**Connectable under residual pressure** Pressure in male side only
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Foundation, Paper, Packaging, Leather, Utensili idraulici, Hydraulic Power Units, Others, Road Construction, Material Handling, Earth Moving, Coil Tubing Unit, Drilling Rig, Demolition, Construction Equipment Attachments, Ceramic, Construction, Trucks & Vehicles, Oil & Gas

Performance	METRIC
ISO DN (mm)	12.5
Max. Flow suggested (l/min)	90
Max. Operating pressure - coupled (MPa)	33
Operating pressure - uncoupled (MPa)	33
Burst pressure - coupled (MPa)	100
Burst pressure - uncoupled (MPa)	100
Connect force (N)	170
Disconnect force (N)	55
Spillage (ml)	0.02

Dimensions	METRIC
Port (A)	3/4"
Overall length M+F (mm)	F+D-17,3
Length (mm)	83,8
Max. diameter (mm)	38
Weight (kg)	0,48

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service