F AX17N S20

Codice articolo: **808509002** / **Female**

Valving style Flat face	**Body size** 3/4"
Sealing Nitrile NBR	**Interchange** ISO 16028
Connection system Push	**Disconnection system** Pull back the sleeve
Material Stainless steel	**Locking mechanism** Locking ball + Safety lock
Disconnectable under pressure No	**Thread** MALE THREAD METRIC S - 24° CONE (ISO 8434-1 & DIN 2353)
Connectable under residual pressure No	**Temperature** -20 / +100 °C; -4 / +212 °F
Applications Medical devices, Semiconductors, Leather, Food Beverage, Defence, Laser, Electric Vehicles, Digital Transmitters, Injection Molding, Die Casting, Others, Marine, Chemical Pharma, Windmill, Test Bench, Steel Mill, Rail, Data Center, Coil Tubing Unit, Drilling Rig, Oil & Gas	

Performance	IMPERIAL
ISO DN (mm)	19
Max. Flow suggested (gpm)	5.3
Max. Operating pressure - coupled (psi)	4785
Operating pressure - uncoupled (psi)	4785
Connect force (lbf)	57.375
Disconnect force (lbf)	18
Spillage (ml)	0.03

Dimensions	IMPERIAL
Port (A)	M30x2
Overall length M+F (in)	7,33
Length (in)	4,31
Max. diameter (in)	1,89
Weight (lb)	2,24

Related products

Product code	Type	Product name
808509003	Maschio	M AX17N S20

Caps

Product code	Product name
815100010	PLASTIC CAP F FF34 RED
815200008	PLASTIC FLIP CAP F FF34 RED
816005010	ALUMINUM CAP F FF34 NATURAL
815101010	PLASTIC CAP F FF34 YELLOW*
815102010	PLASTIC CAP F FF34 BLUE*
815103010	PLASTIC CAP F FF34 BLACK*
815104010	PLASTIC CAP F FF34 GREEN*
815105010	PLASTIC CAP F FF34 WHITE*
815107006	PLASTIC CAP F FF34 ORANGE*
815110006	PLASTIC CAP F FF34 MAGENTA*
815201008	PLASTIC FLIP CAP F FF34 YELLOW*
815202008	PLASTIC FLIP CAP F FF34 BLUE*
815203008	PLASTIC FLIP CAP F FF34 BLACK*
815204008	PLASTIC FLIP CAP F FF34 GREEN*

**Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service