F AX13N S16*

Codice articolo: **808509006** / **Female** / ***Prodotto disponibile su richiesta**

Stucchi®

Valving style
Flat face

Body size
1/2"

Sealing
Nitrile NBR

Interchange
ISO 16028

Connection system
Push

Disconnection system
Pull back the sleeve

Material
Stainless steel

Locking mechanism
Locking ball + Safety lock

Disconnectable under pressure
No

Thread
MALE THREAD METRIC S - 24° CONE (ISO 8434-1 & DIN 2353)

Connectable under residual pressure
No

Temperature
-20 / +100 °C; -4 / +212 °F

Applications
Medical devices, Semiconductors, Leather, Food Beverage, Defence, Laser, Electric Vehicles, Digital Transmitters, Injection Molding, Die Casting, Others, Marine, Chemical Pharma, Windmill, Test Bench, Steel Mill, Rail, Data Center, Coil Tubing Unit, Drilling Rig, Oil & Gas

Performance	IMPERIAL
ISO DN (mm)	12.5
Max. Flow suggested (gpm)	23.85
Max. Operating pressure - coupled (psi)	4785
Operating pressure - uncoupled (psi)	4785
Connect force (lbf)	37.125
Disconnect force (lbf)	13.05
Spillage (ml)	0.02

Dimensions	IMPERIAL
Port (A)	M24X1.5
Overall length M+F (in)	6,74
Length (in)	3,24
Max. diameter (in)	1,57
Weight (lb)	1,01

Caps

Product code	Product name
815100004	PLASTIC CAP F FF12 RED
815200004	PLASTIC FLIP CAP F FF12 RED
816005006	ALUMINUM CAP F FF12 NATURAL
815101004	PLASTIC CAP F FF12 YELLOW**
815102004	PLASTIC CAP F FF12 BLUE**
815103004	PLASTIC CAP F FF12 BLACK**
815104004	PLASTIC CAP F FF12 GREEN**
815105004	PLASTIC CAP F FF12 WHITE**
815201004	PLASTIC FLIP CAP F FF12 YELLOW**
815202004	PLASTIC FLIP CAP F FF12 BLUE**
815203004	PLASTIC FLIP CAP F FF12 BLACK**
815204004	PLASTIC FLIP CAP F FF12 GREEN**
815207004	PLASTIC FLIP CAP F FF12 ORANGE**
815208004	PLASTIC FLIP CAP F FF12 BROWN**

***Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service