
F IRC14XPL BSP*

Codice articolo: **808900116** / **Female** / ***Prodotto disponibile su richiesta**



Valving style Poppet	**Body size** 1/4"
Sealing FKM (VITON)	**Interchange** Similar couplings (Nordic)
Connection system Pull back the sleeve and push	**Disconnection system** Pull back the sleeve
Material Stainless steel (AISI 316L)	**Locking mechanism** Locking ball + Safety sleeve
Disconnectable under pressure No	**Thread** FEMALE THREAD BSPP (ISO 1179-1)
Connectable under residual pressure No	**Temperature** -15 / +180 °C; +5 / +356 °F
Applications Agricultural Machinery, Agricultural Attachments, Construction Equipment Attachments, Demolition, Earth Moving, Foundation, Material Handling, Road Construction, Utensili idraulici, Construction, Agriculture, Trucks & Vehicles	

Performance	IMPERIAL
ISO DN (mm)	6.3
Max. Flow suggested (gpm)	6.36
Max. Operating pressure - coupled (psi)	4350
Operating pressure - uncoupled (psi)	4350
Burst pressure - coupled (psi)	17400
Burst pressure - uncoupled (psi)	17400
Connect force (lbf)	13.5
Disconnect force (lbf)	6.75
Spillage (ml)	1.1

Dimensions	IMPERIAL
Port (A)	1/4"
Overall length M+F (in)	3,22
Length (in)	2,43
Max. diameter (in)	1,02
Weight (lb)	0,34

Related products

Product code	Type	Product name
808900117	Maschio	M IRC14XPL BSP

Spare kits

Product code	Product name
815700978	SPARE KIT OR VITON+BK F IRC14

Caps

Product code	Product name
815000042	PLASTIC CAP F IRC14 RED

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service