
M I34 L22 SCHOTT 36

Codice articolo: **809410029** / **Male**



Valving style Poppet	**Body size** 3/4"
Sealing Nitrile NBR	**Treatment** Cr3
Interchange ISO 7241 A	**Connection system** Push
Disconnection system Pull	**Material** Carbon steel
Locking mechanism Locking ball	**Disconnectable under pressure** No
Thread MALE THREAD METRIC L SCHOTT - 24° CONE BULKHEAD (ISO 8434-1 & DIN 2353)	**Connectable under residual pressure** No
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Agricultural Machinery, Agricultural Attachments, Agriculture

Performance	METRIC
ISO DN (mm)	19
Max. Flow suggested (l/min)	148
Max. Operating pressure - coupled (MPa)	25
Operating pressure - uncoupled (MPa)	25
Burst pressure - coupled (MPa)	90
Burst pressure - uncoupled (MPa)	100
Connect force (N)	130
Disconnect force (N)	70
Spillage (ml)	5.2

Dimensions	METRIC
Port (A)	M30x2
Overall length M+F (mm)	166,5
Length (mm)	83
Max. diameter (mm)	29
Weight (kg)	0,3

Caps

Product code	Product name
815000007	PLASTIC CAP M ISO-A/IR34 RED
815001007	PLASTIC CAP M IR34 YELLOW*
815002007	PLASTIC CAP M IR34 BLUE*
815003007	PLASTIC CAP M IR34 BLACK*
815004007	PLASTIC CAP M IR34 GREEN*
815005007	PLASTIC CAP M IR34 WHITE*
815009017	PLASTIC CAP M ISO-A 34 GREY*

**Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service