
M I12GS S12 SCHOTT

Codice articolo: **809411003** / **Male**



Valving style Poppet	**Body size** 1/2"
Sealing Nitrile NBR	**Treatment** Cr3
Interchange ISO 7241 A	**Connection system** Push
Disconnection system Pull	**Material** Carbon steel
Locking mechanism Locking ball	**Disconnectable under pressure** No
Thread MALE THREAD METRIC S SCHOTT - 24° CONE BULKHEAD (ISO 8434-1 & DIN 8353)	**Connectable under residual pressure** No
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Agricultural Machinery, Agricultural Attachments, Agriculture

Performance	METRIC
ISO DN (mm)	12.5
Max. Flow suggested (l/min)	90
Max. Operating pressure - coupled (MPa)	25
Operating pressure - uncoupled (MPa)	25
Burst pressure - coupled (MPa)	90
Burst pressure - uncoupled (MPa)	100
Connect force (N)	90
Disconnect force (N)	80
Spillage (ml)	1.8

Dimensions	METRIC
Port (A)	M20X1.5
Overall length M+F (mm)	133
Length (mm)	73,3
Max. diameter (mm)	20,5
Weight (kg)	0,15

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service