F IP100 S25 SCHOTT

Codice articolo: **809411016** / **Female**

Valving style Poppet	**Body size** 1"
Sealing Nitrile NBR	**Treatment** Cr3
Interchange ISO 7241 A	**Connection system** Push
Disconnection system Pull	**Material** Carbon steel
Locking mechanism Locking ball	**Disconnectable under pressure** No
Thread MALE THREAD METRIC S SCHOTT - 24° CONE BULKHEAD (ISO 8434-1 & DIN 8353)	**Connectable under residual pressure** No
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Agricultural Machinery, Agricultural Attachments, Agriculture

Performance	METRIC
ISO DN (mm)	25
Max. Flow suggested (l/min)	200
Max. Operating pressure - coupled (MPa)	25
Operating pressure - uncoupled (MPa)	25
Burst pressure - coupled (MPa)	80
Burst pressure - uncoupled (MPa)	100
Connect force (N)	300
Disconnect force (N)	70
Spillage (ml)	1.3

Dimensions	METRIC
Port (A)	M36X2
Overall length M+F (mm)	190,6
Length (mm)	129
Max. diameter (mm)	54
Weight (kg)	0,98

Spare kits

Product code	Product name
815700932	SPARE KIT OR NBR+BK F IP100

Caps

Product code	Product name
815000008	PLASTIC PLUG F ISO-A/IR100 RED
815001018	PLASTIC PLUG F ISO-A 100 YELLOW *
815002018	PLASTIC PLUG F ISO-A 100 BLUE *
815003018	PLASTIC PLUG F ISO-A 100 BLACK *
815004018	PLASTIC PLUG F ISO-A 100 GREEN *
815005018	PLASTIC PLUG F ISO-A 100 WHITE *

**Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service