
F VD114 L42 SCHOTT*

Codice articolo: **809510040** / **Female** / ***Prodotto disponibile su richiesta**



Valving style Poppet	**Body size** 1-1/4"
Sealing Nitrile NBR	**Treatment** Cr3
Interchange ISO 14541	**Connection system** Screw
Disconnection system Unscrew	**Material** Carbon steel
Locking mechanism Screw to connect	**Disconnectable under pressure** No
Thread MALE THREAD METRIC L SCHOTT - 24° CONE BULKHEAD (ISO 8434-1 & DIN 2353)	**Connectable under residual pressure** Pressure in one side
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Construction Equipment Attachments, Demolition, Earth Moving, Foundation, Material Handling, Road Construction, Utensili idraulici, Construction, Trucks & Vehicles

Performance	IMPERIAL
Max. Flow suggested (gpm)	100.17
Max. Operating pressure - coupled (psi)	4350
Operating pressure - uncoupled (psi)	4350
Burst pressure - coupled (psi)	14500
Burst pressure - uncoupled (psi)	14500
Spillage (ml)	51
Manual connect torque (lbf ft)	3.685
Manual disconnect torque (lbf ft)	3.685

Dimensions	IMPERIAL
Port (A)	42.3
Overall length M+F (in)	8,46
Length (in)	5,13
Max. diameter (in)	2,4
Weight (lb)	3,78

Related products

Product code	Type	Product name
809510041	Maschio	M VD114 L42 SCHOTT

Spare kits

Product code	Product name
815700910	SPARE KIT OR NBR+BK+EXT F VD114

Caps

Product code	Product name
814900018	PLASTIC CAP F VD114 RED

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service