
M A15ZN 3/4 NPT









Body size 5/8"	Valving style Flat face
Interchange ISO 16028	Sealing Nitrile NBR
Connection system Push	Disconnection system Pull back the sleeve
Material Carbon steel	Treatment Zn-Ni
Locking mechanism Locking ball + Safety lock	Disconnectable under pressure No
Thread FEMALE THREAD NPT (ANSI B.1.20.1)	Connectable under residual pressure No
Temperature -20 / +100 °C; -4 / +212 °F	Applications Earth moving, Agriculture, Vehicles, Oil & Gas, Industry, Hydraulic Tools

Performance	IMPERIAL
ISO DN (mm)	16
Flow (gpm)	From 13,25 to 39,75
Max. Flow suggested (gpm)	39.22
Max. Operating pressure - coupled (psi)	4785
Operating pressure - uncoupled (psi)	4785
Burst pressure - coupled (psi)	14500
Burst pressure - uncoupled (psi)	14500
Connect force (lbf)	42.75
Disconnect force (lbf)	12.375
Spillage (ml)	0.02

Dimensions	IMPERIAL
Port (A)	3/4"
Overall length M+F (in)	5,49
Length (in)	2,87
Max. diameter (in)	1,06
Weight (lb)	0,7

Related products

Product code	Туре	Product name
809701012	Femmina	F A15ZN 3/4 NPT

Spare kits

Product code	Product name
815700341	SPARE KIT OR NBR+BK M FF 58

Caps

Product code	Product name
815100011	PLASTIC CAP M FF58 RED
816005009	ALUMINUM CAP M FF58 NATURAL
815103011	PLASTIC CAP M FF58 BLACK**
815102011	PLASTIC CAP M FF58 BLUE**
815104011	PLASTIC CAP M FF58 GREEN**
815110011	PLASTIC CAP M FF58 MAGENTA**
815107011	PLASTIC CAP M FF58 ORANGE **
815105011	PLASTIC CAP M FF58 WHITE**
815101011	PLASTIC CAP M FF58 YELLOW**

^{**}Product available upon request