M A15ZN L15*

Codice articolo: **809708019** / **Male** / ***Prodotto disponibile su richiesta**

Valving style Flat face	**Body size** 5/8"
Sealing Nitrile NBR	**Treatment** Zn-Ni
Interchange ISO 16028	**Connection system** Push
Disconnection system Pull back the sleeve	**Material** Carbon steel
Locking mechanism Locking ball + Safety lock	**Disconnectable under pressure** No
Thread MALE THREAD METRIC L - 24° CONE (ISO 8434-1 & DIN 2353)	**Connectable under residual pressure** No
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Construction, Agriculture, Trucks & Vehicles, Oil & Gas

Performance	METRIC
ISO DN (mm)	16
Max. Flow suggested (l/min)	148
Max. Operating pressure - coupled (MPa)	33
Operating pressure - uncoupled (MPa)	33
Burst pressure - coupled (MPa)	100
Burst pressure - uncoupled (MPa)	100
Connect force (N)	190
Disconnect force (N)	55
Spillage (ml)	0.02

Dimensions	METRIC
Port (A)	M22x1.5
Overall length M+F (mm)	139,9
Length (mm)	73
Max. diameter (mm)	27
Weight (kg)	0,29

Spare kits

Product code	Product name
815700341	SPARE KIT OR NBR+BK M FF 58

Caps

Product code	Product name
815100011	PLASTIC CAP M FF58 RED
816005009	ALUMINUM CAP M FF58 NATURAL
815101011	PLASTIC CAP M FF58 YELLOW**
815102011	PLASTIC CAP M FF58 BLUE**
815103011	PLASTIC CAP M FF58 BLACK**
815104011	PLASTIC CAP M FF58 GREEN**
815105011	PLASTIC CAP M FF58 WHITE**
815107011	PLASTIC CAP M FF58 ORANGE**
815110011	PLASTIC CAP M FF58 MAGENTA**

***Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service