# M A15ZN L15*

Codice articolo: **809708019** / **Male** / ***Prodotto disponibile su richiesta**

| | |
|---|---|
| **Valving style**<br>Flat face | **Body size**<br>5/8" |
| **Sealing**<br>Nitrile NBR | **Treatment**<br>Zn-Ni |
| **Interchange**<br>ISO 16028 | **Connection system**<br>Push |
| **Disconnection system**<br>Pull back the sleeve | **Material**<br>Carbon steel |
| **Locking mechanism**<br>Locking ball + Safety lock | **Disconnectable under pressure**<br>No |
| **Thread**<br>MALE THREAD METRIC L - 24° CONE (ISO 8434-1 & DIN 2353) | **Connectable under residual pressure**<br>No |
| **Temperature**<br>-20 / +100 °C; -4 / +212 °F | **Applications**<br>Construction, Agriculture, Trucks & Vehicles, Oil & Gas |

| Performance | IMPERIAL |
|---|---|
| ISO DN (mm) | 16 |
| Max. Flow suggested (gpm) | 39.22 |
| Max. Operating pressure - coupled (psi) | 4785 |
| Operating pressure - uncoupled (psi) | 4785 |
| Burst pressure - coupled (psi) | 14500 |
| Burst pressure - uncoupled (psi) | 14500 |
| Connect force (lbf) | 42.75 |
| Disconnect force (lbf) | 12.375 |
| Spillage (ml) | 0.02 |

| Dimensions | IMPERIAL |
|---|---|
| Port (A) | M22x1.5 |
| Overall length M+F (in) | 5,51 |
| Length (in) | 2,87 |
| Max. diameter (in) | 1,06 |
| Weight (lb) | 0,63 |

## Spare kits

| Product code | Product name |
|---|---|
| 815700341 | SPARE KIT OR NBR+BK M FF 58 |

## Caps

| Product code | Product name |
|---|---|
| 815100011 | PLASTIC CAP M FF58 RED |
| 816005009 | ALUMINUM CAP M FF58 NATURAL |
| 815101011 | PLASTIC CAP M FF58 YELLOW** |
| 815102011 | PLASTIC CAP M FF58 BLUE** |
| 815103011 | PLASTIC CAP M FF58 BLACK** |
| 815104011 | PLASTIC CAP M FF58 GREEN** |
| 815105011 | PLASTIC CAP M FF58 WHITE** |
| 815107011 | PLASTIC CAP M FF58 ORANGE** |
| 815110011 | PLASTIC CAP M FF58 MAGENTA** |

***Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service