
# F/NIPPLE VOFX112 NPT

Codice articolo: **811201056** / **Nipple**







| | |
|---|---|
| **Valving style**<br>Poppet | **Body size**<br>1-1/2" |
| **Sealing**<br>Nitrile NBR | **Interchange**<br>Similar couplings (Oil&Gas) |
| **Connection system**<br>Screw | **Disconnection system**<br>Unscrew |
| **Material**<br>Stainless steel (AISI 316L) | **Locking mechanism**<br>Screw to connect |
| **Disconnectable under pressure**<br>No | **Thread**<br>FEMALE THREAD NPT (ANSI B.1.20.1) |
| **Connectable under residual pressure**<br>Pressure in one side | **Temperature**<br>-20 / +100 °C; -4 / +212 °F |
| **Applications**<br>Construction Equipment Attachments, Demolition, Drilling Rig, Coil Tubing Unit, Earth Moving, Foundation, Material Handling, Road Construction, Marine, Others, Construction, Oil & Gas | |

| Performance | IMPERIAL |
|---|---|
| ISO DN (mm) | 40 |
| Max. Flow suggested (gpm) | 200.87 |
| Max. Operating pressure - coupled (psi) | 3001.5 |
| Operating pressure - uncoupled (psi) | 3001.5 |
| Burst pressure - coupled (psi) | 12006 |
| Burst pressure - uncoupled (psi) | 9004.5 |
| Spillage (ml) | 82.6 |
| Manual connect torque (lbf ft) | 11.1287 |
| Manual disconnect torque (lbf ft) | 11.2024 |

| Dimensions | IMPERIAL |
|---|---|
| Port (A) | 1-1/2" |
| Overall length M+F (in) | 8,67 |
| Length (in) | 5,95 |
| Max. diameter (in) | 3,25 |
| Weight (lb) | 28,29 |

## Related products

| Product code | Type | Product name |
|---|---|---|
| 811201056 | Nipple | F/NIPPLE VOFX112 NPT |

## Spare kits

| Product code | Product name |
|---|---|
| 815701122 | SPARE KIT OR NBR+BK F VOF112 |
| 815701149 | SPARE KIT INTERNAL PARTS F-M VOFX112 |

## Caps

| Product code | Product name |
|---|---|
| 815405016 | ALUMINUM CAP N VOF112 NATURAL |

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service