
M/COUPLER VOFX200 NPT

Codice articolo: **811201059** / **Coupler**



Valving style Poppet	**Body size** 2"
Sealing Nitrile NBR	**Interchange** Similar couplings (Oil&Gas)
Connection system Screw	**Disconnection system** Unscrew
Material Stainless steel (AISI 316L)	**Locking mechanism** Screw to connect
Disconnectable under pressure No	**Thread** FEMALE THREAD NPT (ANSI B.1.20.1)
Connectable under residual pressure Pressure in one side	**Temperature** -20 / +100 °C; -4 / +212 °F
Applications Construction Equipment Attachments, Demolition, Drilling Rig, Coil Tubing Unit, Earth Moving, Foundation, Material Handling, Road Construction, Marine, Others, Construction, Oil & Gas	

Performance	METRIC
ISO DN (mm)	50
Max. Flow suggested (l/min)	1100
Max. Operating pressure - coupled (MPa)	20.7
Operating pressure - uncoupled (MPa)	20.7
Burst pressure - coupled (MPa)	82.8
Burst pressure - uncoupled (MPa)	62,1
Spillage (ml)	192
Manual connect torque (Nm)	10
Manual disconnect torque (Nm)	10

Dimensions	METRIC
Port (A)	2"
Overall length M+F (mm)	255,2
Length (mm)	154,2
Max. diameter (mm)	182,5
Weight (kg)	1,72

Related products

Product code	Type	Product name
811201059	Coupler	M/COUPLER VOFX200 NPT

Spare kits

Product code	Product name
815701150	SPARE KIT INTERNAL PARTS F-M VOFX200

Caps

Product code	Product name
815405019	ALUMINUM CAP P VOF200 NATURAL

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service