
F/NIPPLE VOF114 SAE*

Codice articolo: **811204004** / **Nipple** / ***Prodotto disponibile su richiesta**



Valving style Poppet	**Body size** 1-1/4"
Sealing Nitrile NBR	**Treatment** Cr3
Interchange Similar couplings (Oil&Gas)	**Connection system** Screw
Disconnection system Unscrew	**Material** Carbon steel
Locking mechanism Screw to connect	**Disconnectable under pressure** No
Thread FEMALE THREAD SAE (ISO 11926-1 & SAE J1926-1)	**Connectable under residual pressure** Pressure in one side
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Construction Equipment Attachments, Demolition, Drilling Rig, Coil Tubing Unit, Earth Moving, Foundation, Material Handling, Road Construction, Construction, Oil & Gas

Performance	IMPERIAL
ISO DN (mm)	31.5
Max. Flow suggested (gpm)	152.64
Max. Operating pressure - coupled (psi)	5002.5
Operating pressure - uncoupled (psi)	5002.5
Burst pressure - coupled (psi)	19995.5
Burst pressure - uncoupled (psi)	14500
Spillage (ml)	42.3
Manual connect torque (lbf ft)	2.0636
Manual disconnect torque (lbf ft)	1.4003

Dimensions	IMPERIAL
Port (A)	1-5/8-12UN
Overall length M+F (in)	7,79
Length (in)	5,38
Max. diameter (in)	2,63
Weight (lb)	0,61

Related products

Product code	Type	Product name
811204004	Nipple	F/NIPPLE VOF114 SAE

Spare kits

Product code	Product name
815700960	SPARE KIT OR NBR+BK F VOF114
815700961	SPARE KIT INTERNAL PARTS F-M VOF114

Caps

Product code	Product name
815405014	ALUMINUM CAP N VOF114 NATURAL

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service