
F IRC34PC NPTF Codice articolo: 812102014 / Female





Body size	Valving style
3/4"	Poppet
Interchange	Sealing
Similar couplings (Nordic)	Nitrile NBR
Connection system	Disconnection system
Pull back the sleeve and push	Pull back the sleeve
Material	Treatment
Carbon steel	Zn-Ni
Locking mechanism Locking ball + Safety sleeve	Disconnectable under pressure
Thread	Connectable under residual pressure
FEMALE THREAD NPTF (ANSI B.1.20.3)	Pressure in one side
Temperature	Applications
-20 / +100 °C; -4 / +212 °F	Earth moving, Agriculture, Vehicles, Hydraulic Tools
Similar couplings (Nordic) Connection system Pull back the sleeve and push Material Carbon steel Locking mechanism Locking ball + Safety sleeve Thread FEMALE THREAD NPTF (ANSI B.1.20.3) Temperature	Nitrile NBR Disconnection system Pull back the sleeve Treatment Zn-Ni Disconnectable under pressure No Connectable under residual pressure Pressure in one side Applications

Performance	IMPERIAL
ISO DN (mm)	20
Flow (gpm)	From 39,75 to 92,75
Max. Flow suggested (gpm)	56.18
Max. Operating pressure - coupled (psi)	4785
Operating pressure - uncoupled (psi)	3625
Burst pressure - coupled (psi)	14500
Burst pressure - uncoupled (psi)	11600
Connect force (lbf)	38.25
Disconnect force (lbf)	10.125
Spillage (ml)	15

Dimensions	IMPERIAL
Port (A)	3/4"
Overall length M+F (in)	3,72
Length (in)	3
Max. diameter (in)	2,05
Weight (lb)	1,36

Related products

Product code	Туре	Product name
812102015	Maschio	M IRC34PC NPTF
Spare kits		
Product code	Product name	
815700706	SPARE KIT OR NBR+BK F IRC34	
Caps		
Product code	Product name	
815000048	PLASTIC CAP F IRC34 RED	

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved. Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service