
F IRC100PC NPTF Codice articolo: 812102016 / Female





Body size	Valving style
1"	Poppet
Interchange	Sealing
Similar couplings (Nordic)	Nitrile NBR
Connection system	Disconnection system
Pull back the sleeve and push	Pull back the sleeve
Material	Treatment
Carbon steel	Zn-Ni
Locking mechanism	Disconnectable under pressure
Locking ball + Safety sleeve	No
Thread	Connectable under residual pressure
FEMALE THREAD NPTF (ANSI B.1.20.3)	Pressure in one side
Temperature	Applications
-20 / +100 °C; -4 / +212 °F	Earth moving, Agriculture, Vehicles, Hydraulic Tools

Performance	METRIC
ISO DN (mm)	25
Flow (I/min)	Da 350 a 600
Max. Flow suggested (I/min)	378
Max. Operating pressure - coupled (Mpa)	33
Operating pressure - uncoupled (mpa)	25
Burst pressure - coupled (mpa)	100
Burst pressure - uncoupled (mpa)	100
Connect force (N)	210
Disconnect force (N)	45
Spillage (ml)	18

Dimensions	METRIC
Port (A)	1"
Overall length M+F (mm)	113,4
Length (mm)	92
Max. diameter (mm)	62
Weight (kg)	1,03

Related products

Product code	Туре	Product name
812102017	Maschio	M IRC100PC NPTF
Spare kits		
Product code	Product name	
815700708	SPARE KIT OR NBR+BK F IRC100	
Caps		
Product code	Product name	
815000050	PLASTIC CAP F IRC100 RED	

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved. Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service