

F IRC100PC NPTF











Body size	Valving style
1"	Poppet
Interchange	Sealing
Similar couplings (Nordic)	Nitrile NBR
Connection system Pull back the sleeve and push	Disconnection system Pull back the sleeve
Material	Treatment
Carbon steel	Zn-Ni
Locking mechanism	Disconnectable under pressure
Locking ball + Safety sleeve	No
Thread	Connectable under residual pressure
FEMALE THREAD NPTF (ANSI B.1.20.3)	Pressure in one side
Temperature -20 / +100 °C; -4 / +212 °F	Applications Earth moving, Agriculture, Vehicles, Hydraulic Tools

Performance	IMPERIAL
ISO DN (mm)	25
Flow (gpm)	From 92,75 to 159
Max. Flow suggested (gpm)	100.17
Max. Operating pressure - coupled (psi)	4785
Operating pressure - uncoupled (psi)	3625
Burst pressure - coupled (psi)	14500
Burst pressure - uncoupled (psi)	14500
Connect force (lbf)	47.25
Disconnect force (lbf)	10.125
Spillage (ml)	18

Dimensions	IMPERIAL
Port (A)	1"
Overall length M+F (in)	4,46
Length (in)	3,62
Max. diameter (in)	2,44
Weight (lb)	2,27

Related products

Product code	Туре	Product name
812102017	Maschio	M IRC100PC NPTF

Spare kits

Product code	Product name
815700708	SPARE KIT OR NBR+BK F IRC100

Caps

Product code	Product name
815000050	PLASTIC CAP F IRC100 RED