M IR34FA NPTF*

Codice articolo: **820002021** / **Male** / ***Prodotto disponibile su richiesta**

Valving style Ball	**Body size** 3/4"
Sealing Nitrile NBR	**Treatment** Cr3
Interchange Similar couplings (IR)	**Connection system** Pull back the sleeve and push
Disconnection system Pull back the sleeve	**Material** Carbon steel
Locking mechanism Locking ball	**Disconnectable under pressure** No
Thread FEMALE THREAD NPTF (ANSI B.1.20.3)	**Connectable under residual pressure** No
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Agricultural Machinery, Agricultural Attachments, Agriculture

Performance

	METRIC
Max. Flow suggested (l/min)	148
Max. Operating pressure - coupled (MPa)	25
Operating pressure - uncoupled (MPa)	20
Burst pressure - coupled (MPa)	100
Burst pressure - uncoupled (MPa)	60
Connect force (N)	190
Disconnect force (N)	45
Spillage (ml)	4.5

Dimensions

	METRIC
Port (A)	3/4"
Overall length M+F (mm)	106,5
Length (mm)	53
Max. diameter (mm)	39,1
Weight (kg)	0,19

Related products

Product code	Type	Product name
820002020	Femmina	F IR34FA NPTF

Caps

Product code	Product name
815001007	PLASTIC CAP M IR34 YELLOW**

***Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service