
M VP17PZN 1 SAE

Codice articolo: **811004013** / **Male**



Valving style Flat face	**Body size** 3/4"
Sealing Nitrile NBR	**Treatment** Zn-Ni
Interchange Stucchi profile VP	**Connection system** Screw
Disconnection system Unscrew	**Material** Carbon steel
Locking mechanism Screw to connect + Safety sleeve	**Disconnectable under pressure** Yes
Thread FEMALE THREAD SAE (ISO 11926-1 & SAE J1926-1)	**Connectable under residual pressure** Pressure in both sides
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Construction Equipment Attachments, Demolition, Drilling Rig, Coil Tubing Unit, Earth Moving, Foundation, Material Handling, Road Construction, Utensili idraulici, Construction, Trucks & Vehicles, Oil & Gas

Performance	IMPERIAL
Max. Flow suggested (gpm)	5.3
Max. Operating pressure - coupled (psi)	7250
Operating pressure - uncoupled (psi)	7250
Burst pressure - coupled (psi)	18125
Burst pressure - uncoupled (psi)	18125
Spillage (ml)	0.01
Manual connect torque (lbf ft)	1.474
Manual disconnect torque (lbf ft)	1.0318
Max. residual pressure during connection (in the male, female to drain) (psi)	3625
Max. residual pressure during connection (in the female, male to drain) (psi)	3625
Max. residual pressure during connection (in male and female) (psi)	2175
Max. residual pressure during disconnection (psi)	2175

Dimensions	IMPERIAL
Port (A)	1-5/16-12UN
Overall length M+F (in)	7,97
Length (in)	5
Max. diameter (in)	2,36
Weight (lb)	3,49

Related products

Product code	Type	Product name
811004012	Femmina	F VP17PZN 1 SAE

Spare kits

Product code	Product name
815700655	SPARE KIT OR NBR+BK M FF 34

Caps

Product code	Product name
815305059	ALUMINUM PLUG M VP17 NATURAL
815300059	ALUMINUM PLUG M VP17 RED*
815301059	ALUMINUM PLUG M VP17 YELLOW*
815302059	ALUMINUM PLUG M VP17 BLUE*
815303059	ALUMINUM PLUG M VP17 BLACK*
815304059	ALUMINUM PLUG M VP17 GREEN*

**Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service