# F UQD02B 1/4 HB

Codice articolo: **813723234** / **Hembra**

| | |
|---|---|
| **Estilo de válvula**<br>Cara plana | **Dimensión**<br>02 |
| **Sellado**<br>EPDM | **Intercambio**<br>OCP |
| **Sistema de conexión**<br>Push | **Sistema de desconexión**<br>Tirar el manguito hacia atrás |
| **Material**<br>Acciaio inossidabile (AISI 303) | **Mecanismo de bloqueo**<br>Perno di ritenuta |
| **Desconexión con presión**<br>No | **Roscas**<br>HOSE BARB COMPATIBLE WITH PARKER PUSH-LOK® |
| **Conexión con presión residual**<br>No | **Temperatura**<br>-40 / +75 °C; -40 / +167 °F |
| **Aplicaciones**<br>Centro de datos | |

| Rendimiento | IMPERIAL |
|---|---|
| Presión de trabajo máxima - acoplado (psi) | 160 |
| Presión de trabajo - desacoplado (psi) | 160 |
| Presión de ruptura - acoplado (psi) | 580 |
| Presión de ruptura - acoplado (psi) | 580 |
| Fuerza de conexión (lbf) | 14 |
| Pérdida (ml) | 0,01 |

| Tamaño | IMPERIAL |
|---|---|
| Dimensión roscas (A) | 8.3 |
| Longitud total M+F (in) | 2,7 |
| Longitud (in) | 2,16 |
| Diámetro máximo (in) | 0,79 |
| Peso (lb) | 0,07 |

## Productos relacionados

| Código de producto | Tipologia | Nombre del producto |
|---|---|---|
| 813704235 | Maschio | M UQD02B 1/4 SAE EXT |

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service