F UQD06B 1/2 HB

Codice articolo: **813723250** / **Hembra**

Estilo de válvula Cara plana	**Dimensión** 06
Sellado EPDM	**Intercambio** OCP
Sistema de conexión Push	**Sistema de desconexión** Tirar el manguito hacia atrás
Material Acciaio inossidabile (AISI 303)	**Mecanismo de bloqueo** Perno di ritenuta
Desconexión con presión No	**Roscas** HOSE BARB COMPATIBLE WITH PARKER PUSH-LOK®
Conexión con presión residual No	**Temperatura** -40 / +75 °C; -40 / +167 °F
Aplicaciones Centro de datos	

Rendimiento	IMPERIAL
Presión de trabajo máxima - acoplado (psi)	160
Presión de trabajo - desacoplado (psi)	160
Presión de ruptura - acoplado (psi)	580
Presión de ruptura - acoplado (psi)	580
Fuerza de conexión (lbf)	18
Pérdida (ml)	0,02

Tamaño	IMPERIAL
Dimensión roscas (A)	15.2
Longitud total M+F (in)	4,1
Longitud (in)	3,3
Diámetro máximo (in)	1,2
Peso (lb)	0,21 0,37

Productos relacionados

Código de producto	Tipologia	Nombre del producto
813704251	Maschio	M UQD06B 1/2 SAE EXT

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service