


F IV38HP 1/4 NPT EXT

Codice articolo: **800201006** / **Hembra**







Estilo de válvula Bola	**Dimensión** 3/8"
Sellado Nitrile NBR	**Tratamiento** Cr3
Intercambio ISO14540 (Presión alta)	**Sistema de conexión** Atornillar
Sistema de desconexión Desatornillar	**Material** Acero al carbono
Mecanismo de bloqueo Tornillo	**Desconexión con presión** No
Roscas MALE THREAD NPT (ANSI B1.20.1)	**Conexión con presión residual** No
Temperatura -20 / +100 °C; -4 / +212 °F	**Aplicaciones** Equipos de rescate, Utensili idraulici

Rendimiento	METRIC
Caudal máximo (l/min)	23
Presión de trabajo máxima - acoplado (MPa)	70

Tamaño	METRIC
Dimensión roscas (A)	1/4"
Longitud total M+F (mm)	F+D-18,8
Longitud (mm)	72,3
Diámetro máximo (mm)	35
Peso (kg)	0,21

Spare kits

Código de producto	Nombre del producto
815700650	SPARE KIT OR NBR+BK F IV-HP38

Caps

Código de producto	Nombre del producto
815603012	PLASTIC CAP F IVHP38 BLACK
815605002	STEEL CAP F IVHP38 NATURAL

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service