F IFR8 M18X1.5

Codice articolo: **800212000** / **Hembra**

Estilo de válvula Cara plana non spill	**Dimensión** 3/8"
Sellado Nitrile NBR	**Tratamiento** Cr3
Intercambio ISO 5676 "NF U 16-006"	**Sistema de conexión** Tirar el manguito hacia atrás y empujar
Sistema de desconexión Tirar el manguito hacia atrás	**Material** Acero al carbono
Mecanismo de bloqueo Bola de bloqueo	**Desconexión con presión** No
Roscas FEMALE THREAD METRIC	**Conexión con presión residual** No
Temperatura -20 / +100 °C; -4 / +212 °F	**Aplicaciones** Maquinaria agrícola, Implementos agrícolas, Agricultura

Rendimiento	IMPERIAL
ISO DN (mm)	6.3
Caudal máximo (gpm)	12.19
Presión de trabajo máxima - acoplado (psi)	2175
Presión de trabajo - desacoplado (psi)	2175
Presión de ruptura - acoplado (psi)	14500
Presión de ruptura - acoplado (psi)	4350
Fuerza de conexión (lbf)	38.25
Fuerza de desconexión (lbf)	6.075
Pérdida (ml)	0.06

Tamaño	IMPERIAL
Dimensión roscas (A)	M18x1.5
Longitud total M+F (in)	F+D-0,59
Longitud (in)	2,13
Diámetro máximo (in)	1,73
Peso (lb)	0,88

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service