M UQD02R 1/4 SAE EXT

Codice articolo: **813704201** / **Mâle**

Type de clapet Face plane	**Dimension cupleur** 02
Joint EPDM	**Interchangeabilité** OCP
Système de connexion Pousser	**Système de déconnexion** Retrait manuel de la bague
Matière Acciaio inossidabile (AISI 303)	**Verrouillage** Perno di ritenuta
Déconnexion sous pression No	**Filetage** FEMALE THREAD SAE (ISO 11926-1 & SAE J1926-1)
Connexion avec pression résiduelle No	**Température** -40 / +75 °C; -40 / +167 °F
Applications Data Center	

Performance	IMPERIAL
Pression de service maximale - couplé (psi)	160
Pression de service - découplé (psi)	160
Pression de rupture - couplé (psi)	580
Pression de rupture - découplé (psi)	580
Force de connexion (lbf)	14
Dépôt (ml)	0,01

Dimensions	IMPERIAL
Dimension du filetage (A)	7/16-20 UNF
Longueur totale M+F (in)	2,7
Longueur (in)	1,37
Diamètre maximal (in)	0,61
Poids (lb)	0,31

Produits liés

Code produit	Tipologia	Nom du produit
813723200	Femmina	F UQD02R 1/4 HB

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service