F UQD04R 3/8 HB

Codice articolo: **813723208** / **Femelle**

Type de clapet Face plane	**Dimension cupleur** 04
Joint EPDM	**Interchangeabilité** OCP
Système de connexion Pousser	**Système de déconnexion** Retrait manuel de la bague
Matière Acciaio inossidabile (AISI 303)	**Verrouillage** Perno di ritenuta
Déconnexion sous pression No	**Filetage** HOSE BARB COMPATIBLE WITH PARKER PUSH-LOK®
Connexion avec pression résiduelle No	**Température** -40 / +75 °C; -40 / +167 °F
Applications Data Center	

Performance	METRIC
Pression de service maximale - couplé (MPa)	1,1
Pression de service - découplé (MPa)	1,1
Pression de rupture - couplé (MPa)	4
Pression de rupture - découplé (MPa)	4
Force de connexion (N)	88
Dépôt (ml)	0.01

Dimensions	METRIC
Dimension du filetage (A)	11.9
Longueur totale M+F (mm)	94,5
Longueur (mm)	76,2
Diamètre maximal (mm)	26
Poids (kg)	0,13

Produits liés

Code produit	Tipologia	Nom du produit
813704209	Maschio	M UQD04R 3/8 SAE EXT

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service