F UQD06B 1/2 HB

Codice articolo: **813723250** / **Femelle**

Type de clapet Face plane	**Dimension cupleur** 06
Joint EPDM	**Interchangeabilité** OCP
Système de connexion Pousser	**Système de déconnexion** Retrait manuel de la bague
Matière Acciaio inossidabile (AISI 303)	**Verrouillage** Perno di ritenuta
Déconnexion sous pression No	**Filetage** HOSE BARB COMPATIBLE WITH PARKER PUSH-LOK®
Connexion avec pression résiduelle No	**Température** -40 / +75 °C; -40 / +167 °F
Applications Data Center	

Performance	METRIC
Pression de service maximale - couplé (MPa)	1,1
Pression de service - découplé (MPa)	1,1
Pression de rupture - couplé (MPa)	4
Pression de rupture - découplé (MPa)	4
Force de connexion (N)	80
Dépôt (ml)	0,02

Dimensions	METRIC
Dimension du filetage (A)	15.2
Longueur (mm)	83,3
Diamètre maximal (mm)	31
Poids (kg)	0,1

Produits liés

Code produit	Tipologia	Nom du produit
813704251	Maschio	M UQD06B 1/2 SAE EXT

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service