
M IR38 BSP

Codice articolo: **800000003 / Mâle**



Type de clapet Bille	**Dimension cupleur** 3/8"
Joint Nitrile NBR	**Traitement** Cr3
Interchangeabilité Coupleurs similaires (IR)	**Système de connexion** Retrait manuel de la bague et pousser
Système de déconnexion Retrait manuel de la bague	**Matière** Acier au carbone
Verrouillage Verrouillage à billes	**Déconnexion sous pression** No
Filetage FEMALE THREAD BSPP (ISO 1179-1)	**Connexion avec pression résiduelle** No
Température -20 / +100 °C; -4 / +212 °F	**Applications** Machines agricoles, Équipements agricoles, Agriculture

Performance	METRIC
Débit maximale (l/min)	46
Pression de service maximale - couplé (MPa)	30
Pression de service - découplé (MPa)	30
Pression de rupture - couplé (MPa)	100
Pression de rupture - découplé (MPa)	100
Force de connexion (N)	125
Force de déconnexion (N)	45
Dépôt (ml)	0.45

Dimensions	METRIC
Dimension du filetage (A)	3/8"
Longueur totale M+F (mm)	76,3
Longueur (mm)	38
Diamètre maximal (mm)	19
Poids (kg)	0,08

Produits liés

Code produit	Tipologia	Nom du produit
800000002	Femmina	F IR38 BSP

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service