


F IV38HP 1/4 NPT EXT

Codice articolo: **800201006** / **Femelle**







Type de clapet Bille	**Dimension cupleur** 3/8"
Joint Nitrile NBR	**Traitement** Cr3
Interchangeabilité ISO14540 (Haute pression)	**Système de connexion** Visser
Système de déconnexion Dévisser	**Matière** Acier au carbone
Verrouillage Visser	**Déconnexion sous pression** No
Filetage MALE THREAD NPT (ANSI B1.20.1)	**Connexion avec pression résiduelle** No
Température -20 / +100 °C; -4 / +212 °F	**Applications** Équipements de secours, Outils hydrauliques

Performance	METRIC
Débit maximale (l/min)	23
Pression de service maximale - couplé (MPa)	70

Dimensions	METRIC
Dimension du filetage (A)	1/4"
Longueur totale M+F (mm)	F+D-18,8
Longueur (mm)	72,3
Diamètre maximal (mm)	35
Poids (kg)	0,21

Spare kits

Code produit	Nom du produit
815700650	SPARE KIT OR NBR+BK F IV-HP38

Caps

Code produit	Nom du produit
815603012	PLASTIC CAP F IVHP38 BLACK
815605002	STEEL CAP F IVHP38 NATURAL

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service