F IFR8 M18X1.5 (WITHOUT PLUG)*

Codice articolo: **800212008** / **Femelle** / ***Prodotto disponibile su richiesta**

Stucchi®

Type de clapet Face plane no spill	**Dimension cupleur** 3/8"
Joint Nitrile NBR	**Traitement** Cr3
Interchangeabilité ISO 5676 "NF U 16-006"	**Système de connexion** Retrait manuel de la bague et pousser
Système de déconnexion Retrait manuel de la bague	**Matière** Acier au carbone
Verrouillage Verrouillage à billes	**Déconnexion sous pression** No
Filetage FEMALE THREAD METRIC	**Connexion avec pression résiduelle** No
Température -20 / +100 °C; -4 / +212 °F	**Applications** Machines agricoles, Équipements agricoles, Agriculture

Performance	METRIC
ISO DN (mm)	6.3
Débit maximale (l/min)	46
Pression de service maximale - couplé (MPa)	15
Pression de service - découplé (MPa)	15
Pression de rupture - couplé (MPa)	100
Pression de rupture - découplé (MPa)	30
Force de connexion (N)	170
Force de déconnexion (N)	27
Dépôt (ml)	0.06

Dimensions	METRIC
Dimension du filetage (A)	M18x1.5
Longueur totale M+F (mm)	F+D-15
Longueur (mm)	54,2
Diamètre maximal (mm)	44
Poids (kg)	0,34

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service