M UQD02B 1/4 SAE EXT

Codice articolo: **813704235** / **Maschio**

Sistema di tenuta Faccia piana	**Diametro nominale** 02
Guarnizione EPDM	**Intercambiabilità** OCP
Sistema di connessione Spingere	**Sistema di disconnessione** Tirare indietro la ghiera
Materiale Acciaio inossidabile (AISI 303)	**Meccanismo di bloccaggio** Perno di ritenuta
Disconnessione in pressione No	**Filettatura** FEMALE THREAD SAE (ISO 11926-1 & SAE J1926-1)
Connessione con pressione residua No	**Temperatura** -40 / +75 °C; -40 / +167 °F
Applicazioni Data center	

Performance	IMPERIAL
Pressione di esercizio massima - accoppiato (psi)	160
Pressione di esercizio - disaccoppiato (psi)	160
Pressione di scoppio - accoppiato (psi)	580
Pressione di scoppio - disaccoppiato (psi)	580
Forza di connessione (lbf)	14
Versamento (ml)	0,01

Dimensioni	IMPERIAL
Misura del raccordo (A)	7/16-20 UNF
Lunghezza complessiva M+F (in)	2,7
Lunghezza (in)	1,37
Diametro massimo (in)	0,61
Peso (lb)	0,31

Prodotti correlati

Codice prodotto	Tipologia	Nome prodotto
813723234	Femmina	F UQD02B 1/4 HB

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service