F UQD04R 3/8 HB

Codice articolo: **813723208** / **Femmina**

Sistema di tenuta Faccia piana	**Diametro nominale** 04
Guarnizione EPDM	**Intercambiabilità** OCP
Sistema di connessione Spingere	**Sistema di disconnessione** Tirare indietro la ghiera
Materiale Acciaio inossidabile (AISI 303)	**Meccanismo di bloccaggio** Perno di ritenuta
Disconnessione in pressione No	**Filettatura** HOSE BARB COMPATIBLE WITH PARKER PUSH-LOK®
Connessione con pressione residua No	**Temperatura** -40 / +75 °C; -40 / +167 °F
Applicazioni Data center	

Performance	METRIC
Pressione di esercizio massima - accoppiato (MPa)	1,1
Pressione di esercizio - disaccoppiato (MPa)	1,1
Pressione di scoppio - accoppiato (MPa)	4
Pressione di scoppio - disaccoppiato (MPa)	4
Forza di connessione (N)	88
Versamento (ml)	0,01

Dimensioni	METRIC
Misura del raccordo (A)	11.9
Lunghezza complessiva M+F (mm)	94,5
Lunghezza (mm)	76,2
Diametro massimo (mm)	26
Peso (kg)	0,13

Prodotti correlati

Codice prodotto	Tipologia	Nome prodotto
813704209	Maschio	M UQD04R 3/8 SAE EXT

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service