F UQD04B 3/8 HB

Codice articolo: **813723242** / **Femmina**

Sistema di tenuta Faccia piana	**Diametro nominale** 04
Guarnizione EPDM	**Intercambiabilità** OCP
Sistema di connessione Spingere	**Sistema di disconnessione** Tirare indietro la ghiera
Materiale Acciaio inossidabile (AISI 303)	**Meccanismo di bloccaggio** Perno di ritenuta
Disconnessione in pressione No	**Filettatura** HOSE BARB COMPATIBLE WITH PARKER PUSH-LOK®
Connessione con pressione residua No	**Temperatura** -40 / +75 °C; -40 / +167 °F
Applicazioni Data center	

Performance	IMPERIAL
Pressione di esercizio massima - accoppiato (psi)	160
Pressione di esercizio - disaccoppiato (psi)	160
Pressione di scoppio - accoppiato (psi)	580
Pressione di scoppio - disaccoppiato (psi)	580
Forza di connessione (lbf)	20
Versamento (ml)	0,01

Dimensioni	IMPERIAL
Misura del raccordo (A)	11.9
Lunghezza complessiva M+F (in)	3,72
Lunghezza (in)	3
Diametro massimo (in)	1,02
Peso (lb)	0,29

Prodotti correlati

Codice prodotto	Tipologia	Nome prodotto
813704243	Maschio	M UQD04B 3/8 SAE EXT

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service