


F IV38HP 1/4 NPT EXT

Codice articolo: **800201006** / **Femmina**







Sistema di tenuta Sfera	**Diametro nominale** 3/8"
Guarnizione Nitrile NBR	**Trattamento** Cr3
Intercambiabilità ISO 14540 (Alta pressione)	**Sistema di connessione** Avvitare
Sistema di disconnessione Svitare	**Materiale** Acciaio al carbonio
Meccanismo di bloccaggio A vite	**Disconnessione in pressione** No
Filettatura MALE THREAD NPT (ANSI B1.20.1)	**Connessione con pressione residua** No
Temperatura -20 / +100 °C; -4 / +212 °F	**Applicazioni** Attrezzature di soccorso, Utensili idraulici

Performance	METRIC
Portata massima (l/min)	23
Pressione di esercizio massima - accoppiato (MPa)	70

Dimensioni	METRIC
Misura del raccordo (A)	1/4"
Lunghezza complessiva M+F (mm)	F+D-18,8
Lunghezza (mm)	72,3
Diametro massimo (mm)	35
Peso (kg)	0,21

Spare kits

Codice prodotto	Nome prodotto
815700650	SPARE KIT OR NBR+BK F IV-HP38

Caps

Codice prodotto	Nome prodotto
815603012	PLASTIC CAP F IVHP38 BLACK
815605002	STEEL CAP F IVHP38 NATURAL

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service