
M I12GS 3/8 BSP

Codice articolo: **809400005** / **Maschio**



Sistema di tenuta Funghetto	**Diametro nominale** 1/2"
Guarnizione Nitrile NBR	**Trattamento** Cr3
Intercambiabilità ISO 7241 A	**Sistema di connessione** Spingere
Sistema di disconnessione Tirare	**Materiale** Acciaio al carbonio
Meccanismo di bloccaggio Sfere di sicurezza	**Disconnessione in pressione** No
Filettatura FEMALE THREAD BSPP (ISO 1179-1)	**Connessione con pressione residua** No
Temperatura -20 / +100 °C; -4 / +212 °F	**Applicazioni** Macchine agricole, Attrezzature agricole, Agricoltura

Performance	IMPERIAL
ISO DN (mm)	12,5
Portata massima (gpm)	23,85
Pressione di esercizio massima - accoppiato (psi)	3625
Pressione di esercizio - disaccoppiato (psi)	3625
Pressione di scoppio - accoppiato (psi)	13050
Pressione di scoppio - disaccoppiato (psi)	14500
Forza di connessione (lbf)	20,25
Forza di disconnessione (lbf)	18
Versamento (ml)	1,8

Dimensioni	IMPERIAL
Misura del raccordo (A)	3/8"
Lunghezza complessiva M+F (in)	3,98
Lunghezza (in)	2,26
Diametro massimo (in)	0,81
Peso (lb)	0,31

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service